



CIVIC STANDARD SHELVING GUIDELINES

Our shelving systems are designed to maximise functionality, durability, and ease of use. The following guidelines outline the standard dimensions and installation requirements for wardrobes, pantries, linen cupboards, and similar storage applications.

SHELF DEPTH & SPAN

- Standard shelf depth: 440mm
- Maximum finished shelf depth: 30mm less than the overall recess depth
 - Example: If the recess is 400mm deep, the shelf will be 370mm
- Maximum shelf span: 3600mm (any span longer requires a gable to join the shelf)
- Maximum unsupported shelf span: 1200mm

SUPPORT REQUIREMENTS

- Vertical support posts are required for pantry, linen, or similar shelving when spans exceed 1200mm.
- Support posts must be positioned:
 - 600mm from the internal corner on L-shape or U-shape rooms, and
 - At the centre of the span when greater than 2400mm.
- Front cleats may be used to provide additional strength to shelving.
 - With front cleats, the recommended maximum span between supports is 2000mm (to be confirmed pending further testing).

DRAWER & ADJUSTABLE SHELF TOWERS

- Towers positioned against a wall must include an infill panel.
- This ensures clearance for drawers from any adjacent architraves (including in walk-in robes).

HANGING ROD POSITIONING

- Hanging rod must be a minimum of 250mm from the rear wall.
- Double hanging configurations require a top shelf height of at least 1900mm from finished floor level (FFL), with 2000mm preferred.
- Allow 600mm clearance from corners in L-shape or U-shape rooms for hanging space.

Professional, Reliable, Built to Last
Australian Owned and Family Operated

Precision installation by industry experts
Backed by Civic's quality guarantee